

Technical data

MODEL		DANESMOOR SYSTEM EXTERNAL 12/18	DANESMOOR SYSTEM EXTERNAL 18/25	DANESMOOR SYSTEM EXTERNAL 25/32
Clearances*	Above	600mm	600mm	600mm
	Front	600mm	600mm	600mm
	RH/LH flue outlet on opposite side	10mm	10mm	10mm
	RH flue outlet on rear	45mm	45mm	45mm
	LH flue outlet on rear	85mm	85mm	85mm
	Rear - flue outlet on side	50mm*	50mm*	50mm*
	Rear - rear flue outlet	2,500mm**	2,500mm**	2,500mm**
Output kW to central heating (CH)		12kW - 18kW	18kW - 25kW	25kW - 32kW
ErP Seasonal space heating energy efficiency class		A / 90%	A / 90%	A / 91%
Solar compatible		\checkmark	\checkmark	\checkmark

^{*200}mm if using a high level terminal exiting through the rear panel.

**From end of flue terminal allow 2,500mm clearance.


Accessories

Greenstar System Filter Install a Greenstar System Filter to protect your heating system from contamination and extend your guarantee up to 5 years*.

Boiler dimensions

The Greenstar Danesmoor External's weather proof case features IP45 ingress protection.





Know your system

System boilers require a cylinder for storing hot water, however the major heating and hot water system components are built into the boiler itself, making it quicker and neater to install.