

Product datasheet on energy consumption

Greenstore

7 System LECP

8738203185

The following product data complies with the requirements of EU Regulations 811/2013 and 812/2013 as supplement to the Directive 2010/30/EU.

Productdata	Symbol	Unit	8738203185
Brine-to-water heat pump			Yes
Equipped with a supplementary heater?			Yes
Rated heat output (average climate conditions)	Prated	kW	7
Rated heat output (colder climate conditions)	Prated	kW	8
Rated heat output (warmer climate conditions)	Prated	kW	7
Rated heat output (low temperature application, average climate conditions)	Prated	kW	8
Rated heat output (low temperature application, colder climate conditions)	Prated	kW	7
Rated heat output (low temperature application, warmer climate conditions)	Prated	kW	9
Seasonal space heating energy efficiency (average climate conditions)	η_s	%	107
Seasonal space heating energy efficiency (colder climate conditions)	η_s	%	110
Seasonal space heating energy efficiency (warmer climate conditions)	η_s	%	106
Seasonal space heating energy efficiency (low temperature application, average climate conditions)	η_s	%	148
Seasonal space heating energy efficiency (low temperature application, colder climate conditions)	η_s	%	151
Seasonal space heating energy efficiency (low temperature application, warmer climate conditions)	η_s	%	147
Energy Efficiency Class			A+
Energy efficiency class (low temperature application)			A++
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C (average climate conditions)	Pdh	kW	6,1
Tj = - 7 °C (colder climate conditions)	Pdh	kW	6,2
Tj = - 7 °C (low temperature application, average climate conditions)	Pdh	kW	6,9
Tj = - 7 °C (low temperature application, colder climate conditions)	Pdh	kW	7,1
Tj = + 2 °C (average climate conditions)	Pdh	kW	6,3
Tj = + 2 °C (colder climate conditions)	Pdh	kW	6,5
Tj = + 2 °C (warmer climate conditions)	Pdh	kW	6,0
Tj = + 2 °C (low temperature application, average climate conditions)	Pdh	kW	7,0
Tj = + 2 °C (low temperature application, colder climate conditions)	Pdh	kW	7,1
Tj = + 2 °C (low temperature application, warmer climate conditions)	Pdh	kW	6,9
Tj = + 7 °C (average climate conditions)	Pdh	kW	6,5
Tj = + 7 °C (colder climate conditions)	Pdh	kW	6,7
Tj = + 7 °C (warmer climate conditions)	Pdh	kW	6,2
Tj = + 7 °C (low temperature application, average climate conditions)	Pdh	kW	7,1
Tj = + 7 °C (low temperature application, colder climate conditions)	Pdh	kW	7,2
Tj = + 7 °C (low temperature application, warmer climate conditions)	Pdh	kW	7,0
Tj = + 12 °C (average climate conditions)	Pdh	kW	6,7
Tj = + 12 °C (colder climate conditions)	Pdh	kW	6,8
Tj = + 12 °C (warmer climate conditions)	Pdh	kW	6,6
Tj = + 12 °C (low temperature application, average climate conditions)	Pdh	kW	7,2
Tj = + 12 °C (low temperature application, colder climate conditions)	Pdh	kW	7,2
Tj = + 12 °C (low temperature application, warmer climate conditions)	Pdh	kW	7,2
Tj = bivalent temperature (average climate conditions)	Pdh	kW	6,1
Tj = bivalent temperature (colder climate conditions)	Pdh	kW	6,1

Product datasheet on energy consumption

Greenstore

7 System LECP

8738203185

Productdata	Symbol	Unit	8738203185
Tj = bivalent temperature (warmer climate conditions)	Pdh	kW	6,0
Tj = bivalent temperature (low temperature application, average climate conditions)	Pdh	kW	6,9
Tj = bivalent temperature (low temperature application, colder climate conditions)	Pdh	kW	7,0
Tj = bivalent temperature (low temperature application, warmer climate conditions)	Pdh	kW	6,9
For air-to-water heat pumps: Tj = operation limit temperature	Pdh	kW	6,0
For air-to-water heat pumps: Tj = operation limit temperature (low temperature)	Pdh	kW	6,9
Bivalent temperature (average climate conditions)	T _{biv}	°C	-7
Bivalent temperature (colder climate conditions)	T _{biv}	°C	-15
Bivalent temperature (warmer climate conditions)	T _{biv}	°C	3
Bivalent temperature (low temperature application, average climate conditions)	T _{biv}	°C	-7
Bivalent temperature (low temperature application, colder climate conditions)	T _{biv}	°C	-17
Bivalent temperature (low temperature application, warmer climate conditions)	T _{biv}	°C	3
Degradation co-efficient Tj = - 7 °C	Cdh		1,0
Degradation co-efficient Tj = + 2 °C	Cdh		1,0
Degradation co-efficient Tj = + 7 °C	Cdh		1,0
Degradation co-efficient Tj = + 12 °C	Cdh		1,0
Degradation co-efficient of the operating temperature limit	Cdh		1,0
Degradation co-efficient of the dual-fuel switch-over point	Cdh		1,0
Degradation co-efficient Tj = - 7 °C (low temperature application)	Cdh		1,0
Degradation co-efficient Tj = - 2 °C (low temperature application)	Cdh		1,0
Degradation co-efficient Tj = - 7 °C (low temperature application)	Cdh		1,0
Degradation co-efficient Tj = - 12 °C (low temperature application)	Cdh		1,0
Degradation co-efficient of the operating temperature limit (low temperature application)	Cdh		1,0
Degradation co-efficient of the dual-fuel switch-over point (low temperature application)	Cdh		1,0
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj /			
Tj = - 7 °C	COPd		2,46
Tj = - 7 °C (colder climate conditions)	COPd		2,79
Tj = - 7 °C (low temperature application, average climate conditions)	COPd		3,75
Tj = - 7 °C (low temperature application, colder climate conditions)	COPd		3,96
Tj = + 2 °C (average climate conditions)	COPd		2,83
Tj = + 2 °C (colder climate conditions)	COPd		3,11
Tj = + 2 °C (warmer climate conditions)	COPd		2,99
Tj = + 2 °C (low temperature application, average climate conditions)	COPd		3,91
Tj = + 2 °C (low temperature application, colder climate conditions)	COPd		4,08
Tj = + 2 °C (low temperature application, warmer climate conditions)	COPd		3,67
Tj = + 7 °C (average climate conditions)	COPd		3,15
Tj = + 7 °C (colder climate conditions)	COPd		3,39
Tj = + 7 °C (warmer climate conditions)	COPd		2,65
Tj = + 7 °C (low temperature application, average climate conditions)	COPd		4,06
Tj = + 7 °C (low temperature application, colder climate conditions)	COPd		4,17
Tj = + 7 °C (low temperature application, warmer climate conditions)	COPd		3,86
Tj = + 12 °C (average climate conditions)	COPd		3,46



Product datasheet on energy consumption

Greenstore

7 System LECP

8738203185

Productdata	Symbol	Unit	8738203185
Tj = + 12 °C (colder climate conditions)	COPd		3,59
Tj = + 12 °C (warmer climate conditions)	COPd		3,24
Tj = + 12 °C (low temperature application, average climate conditions)	COPd		4,20
Tj = + 12 °C (low temperature application, colder climate conditions)	COPd		4,19
Tj = + 12 °C (low temperature application, warmer climate conditions)	COPd		4,11
Tj = bivalent temperature (average climate conditions)	COPd		2,46
Tj = bivalent temperature (colder climate conditions)	COPd		2,58
Tj = bivalent temperature (warmer climate conditions)	COPd		2,39
Tj = bivalent temperature (low temperature application, average climate conditions)	COPd		3,75
Tj = bivalent temperature (low temperature application, colder climate conditions)	COPd		3,86
Tj = bivalent temperature (low temperature application, warmer climate conditions)	COPd		3,73
Tj = operation limit temperature	COPd		2,29
Tj = operation limit temperature (low temperature application)	COPd		3,67
Heating water operating limit temperature	WTOL	°C	65
Power consumption in modes other than active mode			
Off mode	P _{OFF}	kW	0,006
Thermostat-off mode	P _{TO}	kW	0,006
In standby mode	P _{SB}	kW	0,006
Crankcase heater mode	P _{CK}	kW	0,000
Supplementary heater			
Rated heat output	P _{sup}	kW	0,9
Rated heat output (colder climate conditions)	P _{sup}	kW	1,5
Rated heat output (warmer climate conditions)	P _{sup}	kW	0,5
Rated heat output (low temperature application, average climate conditions)	P _{sup}	kW	1,0
(low temperature application, colder climate conditions)	P _{sup}	kW	1,7
(low temperature application, warmer climate conditions)	P _{sup}	kW	0,6
Type of energy input			Electric
Other items			
Capacity control			fixed
Sound power level, indoors	L _{WA}	dB	47
Annual energy consumption	Q _{HE}	kWh	4952
Annual energy consumption (colder climate conditions)	Q _{HE}	kWh	3039
Annual energy consumption (warmer climate conditions)	Q _{HE}	kWh	3039
Annual energy consumption (low temperature application, average climate conditions)	Q _{HE}	kWh	4129
Annual energy consumption (low temperature application, colder climate conditions)	Q _{HE}	kWh	5312
Annual energy consumption (low temperature application, warmer climate conditions)	Q _{HE}	kWh	2553
For brine-to-water heat pumps: Rated brine flow rate, outdoor heat exchanger		m ³ /h	1
For brine-to-water heat pumps: Rated brine flow rate, outdoor heat exchanger (low temperature application)		m ³ /h	1

System datasheet on energy consumption

Greenstore

7 System LECP

8738203185

The following system data meets the requirements of EU Regulations no. 811/2013 and no.812/2013 supplementing Directive 2010/30/EU. The energy efficiency given in this data sheet for the product combination may deviate from the energy efficiency after its installation in a building, since this is influenced by other factors such as heat loss in the distribution system and the dimensioning of the products in relation to the size and characteristics of the building.

Information about calculating the space heating energy efficiency		
I	Value for the space heating energy efficiency of the preferential space heater	107 %
II	Factor for the weighting of the heat output of the preferential and supplementary heaters of a package system	0 -
III	Value of the mathematical expression $294/(11 \cdot \text{Prated})$	3.82 -
IV	Value of the mathematical expression $115/(11 \cdot \text{Prated})$	1.49 -
V	Difference between the seasonal space heating energy efficiency with average and colder climate conditions	3 %
VI	Difference between the seasonal space heating energy efficiency with warmer and average climate conditions	1 %

Seasonal space heating energy efficiency of the heat pump **I** = **1** 107 %

Temperature control (From the data sheet of the temperature control) + **2** 1,5 %

Class: I = 1 %, II = 2 %, III = 1.5 %, IV = 2 %, V = 3 %, VI = 4 %, VII = 3.5 %, VIII = 5 %

Supplementary boiler (From the data sheet of the boiler) (- I) x II = - **3** %

Seasonal space heating energy efficiency (in %)

Solar contribution (III x + IV x) x 0,45 x (/100) x = + **4** %

(From the data sheet of the solar device)

Collector size (in m²)

Storage tank volume (in m³)

Collector efficiency (in %)

Storage tank rating: A* = 0.95, A = 0.91, B = 0.86, C = 0.83, D-G = 0.81

Seasonal space heating energy efficiency of the package system

- with average climate conditions: **5** 109 %

Seasonal space heating energy efficiency class of the package system with average climate conditions

G < 30 %, F ≥ 30 %, E ≥ 34 %, D ≥ 36 %, C ≥ 75 %, B ≥ 82 %, A ≥ 90 %, A* ≥ 98 %, A** ≥ 125 %, A*** ≥ 150 %

A*

Seasonal space heating energy efficiency

- with colder climate conditions: **5** 109 - V = 112 %

- with warmer climate conditions: **5** 109 + VI = 108 %

