



The Worcester Greenstar CDi Classic combi

Why install a Greenstar CDi Classic combi?

- ► Highest hot water flow rate of the Greenstar combi wall mounted range
- Instantaneous hot water, always available
- Larger two bathroom properties can be supplied by higher output options
- Wide choice of controls enables greater comfort and economy
- Low energy pump reduces electrical usage
- Inbuilt keyless filling link makes it easy to refill your system if needed



Trustpilot Rated 5 Stars Our customers have

consistently rated us 5 stars on Trustpilot.co.uk



Up to 7 Years Guarantee

Up to 7 years guarantee available on all Worcester Bosch gas boilers*



Royal Warrant

We are honoured to have received a Royal Warrant in recognition of supplying goods to Her Majesty The Queen




BOSCH

Invented for life

Part of the Bosch Group

All products are manufactured with Bosch levels of quality and reliability as standard





Technical data

MODEL		29CDi CLASSIC	34CDi CLASSIC	38CDi CLASSIC	42CDi CLASSIC
Clearances	Above flue	30mm	30mm	30mm	30mm
	Sides	5mm	5mm	5mm	5mm
	Below	200mm	200mm	200mm	200mm
	Front	20mm*	20mm*	20mm*	20mm*
Flow rate at the hot water tap (35°C)		12.3 l/min	14.3 l/min	16.4 l/min	17.2 l/min
Output kW to central heating (CH)		7.7kW - 30kW	7.7kW - 30kW	9.4kW - 30kW	9.4kW - 30kW
Modulating control		\checkmark	\checkmark	\checkmark	\checkmark
Integrated filling link		\checkmark	\checkmark	\checkmark	\checkmark
Condensing in domestic hot water		\checkmark	\checkmark	\checkmark	\checkmark
Intelligent controls		\checkmark	\checkmark	\checkmark	\checkmark

^{*20}mm from a removable cupboard door, 600mm from a fixed surface for servicing.

Same clearances for ventilated and unventilated compartments.

Control options

Mechanical	Comfort	Sense	Easy	
-,O,	No.	218 8	21 22	


Accessories



Boiler dimensions

The Greenstar CDi range is the perfect size to fit between your wall-mounted kitchen cupboards.





Know your system

Combination, or 'combi' boilers, heat water directly from the mains when you turn on a tap, so you won't need a hot water storage cylinder or a cold water storage tank.